

HDT18^{HD}

DVB-C



Main System

Main Chipset : ALi M3711
Flash Memory : 8/ 16MBytes Serial Flash
System Memory : 64/ 128MBytes DDR3

Demodulation

Receiver Standard: DVB-C (EN 300 429)
Demodulation : 16/ 32/ 64/ 128/ 256QAM
Frequency : 47-862MHz
RF Input Level : 40dBuV~90dBuV

Video Decoder

Video Decoding : MPEG1, MPEG2 (MP@HL)
H.264,VC1, DV, MPEG4
Display Resolution : 480i, 480p, 576i, 576p, 720i
720p, 1080i, 1080p
Aspect Ratio : 4:3, 16:9

Audio Decoder

Audio Decoding : MPEG-2 layer I and II (Musiccam)
MPEG4 AAC, Dolby Digital (AC-3)
Audio Mode : Stereo/ Left/ Right
Sampling Rate : 32KHz/ 44.1KHz/ 48KHz

Front Panel

Remote Sensor : 1 x Infra-red Receiver 38KHz
Smart Card : COB
LED Indicator : 2 x LED Indicator (Red/ Blue)

Rear/ Right/ Left Side

Signal Input : 1 x IEC 169-24 F-Type Female
AV Out : 2x L/R+ 1x CVBS
(4 pole earphone jackDC3.5mm)
USB : 1 x Micro USB (For power input 5V/1A)
HDMI : 1 x HDMI

Physical

Operating Temperature Range : 0°C ~ + 45°C
Storage Humidity : 5% ~ 95% RH (Non-condensing)
Dimension : 23 x 57 x 18.5 mm



Features

- DVB-C, MPEG-2, MPEG-4, H.264
- Support ABV CAS
- Favorite Channel List Management
- Channel Search (Automatic/ Manual)
- Multi-language
- Friendly GUI
- Parental Lock
- EPG 7 Days
- Upgrade by OTA